

**GWS250**

SPECIFICATIONS

PA589-01-01

MODEL		GWS250-12	GWS250-24	GWS250-36	GWS250-48	
ITEMS						
1	Nominal Output Voltage	V	12	24	36	48
2	Maximum Output Current	A	21	10.5	7	5.3
3	Peak Output Current (*12)	A	-	12.5	8.4	-
4	Maximum Output Power	W	252	252	252	254.4
5	Peak Output Power (*12)	W	-	300	302.4	-
6	Standby Input Power (*13)	W	0.5			
7	Standby Output	-	5V @ 300mA			
8	Efficiency (Typ) (230VAC) (*1)	%	92	92	93	93
9	Input Voltage Range (*2)	V	85 ~ 264VAC (47-63Hz) or 120 ~ 373VDC (Withstand 300VAC Surge for 5 seconds)			
10	Input Current (Typ) (115/230VAC) (*1)	A	3.0 / 1.4			
11	Inrush Current (Typ) (*3)	A	20A / 115VAC, 40A / 230VAC (Cold Start)			
12	PFHC	-	Designed to meet IEC61000-3-2			
13	Power Factor (Typ) (115/230VAC) (*1)	-	> 0.98 / 0.95			
14	Output Voltage Range	V	10.8~13.2	22~28.8	32~40	42~57.6
15	Ripple & Noise (*1,4)	mV	150	240	360	480
16	Line Regulation (*5,6)	mV	48	96	144	192
17	Load Regulation (*5,7)	mV	96	192	288	384
18	Temperature Coefficient	-	Less than ± 0.02% / °C			
19	Over Current Protection (*8)	-	Hiccup	Constant Current Limit		
20	Over Voltage Protection (*9)	V	13.8~16.2	30.3~35.5	41.4 ~ 48.6	60 ~ 69.6
21	Over Temperature Protection	-	Yes. Shutdown output and manual reset (CNT or Re-power on)			
22	Hold-up Time (Typ) (*1)	ms	16			
23	Leakage Current (*10)	-	< 0.75mA at 240VAC			
24	Remote Sensing	-	-			
25	Remote ON/OFF control	-	Possible (Active Low)			
26	Monitoring Signal	-	DCOK (Open Collector Output - Active Low)			
27	Programmable Voltage	-	Possible			
28	Series Operation	-	Possible			
29	Operating Temperature (*11)	-	-25°C ~ +70°C (Refer to Output Derating Curve)			
30	Operating Humidity	-	30 to 90%RH (No dewdrop)			
31	Storage Temperature	-	-30°C ~ +85°C			
32	Storage Humidity	-	10 to 95%RH (No dewdrop)			
33	Cooling	-	Convection Cooling			
34	Withstand Voltage	-	Input - Output : 3.0kVAC (20mA), Input - FG : 1.5kVAC (20mA) Output - FG : 500VAC (100mA) for 1min.			
35	Isolation Resistance	-	Input - FG, Input - Output and Output - FG More than 100MΩ (500VDC) at 25°C and 70%RH			
36	Vibration	-	At no operating, 10 - 55Hz (sweep for 1min) 19.6m/s <sup>2</sup> Constant, X, Y, Z 1hour each.			
37	Shock (In package)	-	Less than 196.1m/s <sup>2</sup>			
38	Safety	-	Approved by UL60950-1, CSA C22.2 No.60950-1-07 (2nd Edition) EN60950-1, IEC60950-1 (2nd Edition), CE			
39	EMI	-	Built to meet EN55022-B,CISPR22-B			
40	Immunity	-	Built to meet EN61000-4-2 (Level 2,3), -3 (Level 3), -4 (Level 3), -5 (Level 4), -6 (Level 3), -8 (Level 4), -11			
41	Weight(Typ.)	g	850			
42	Size (L x W x D)	mm	198 x 105 x 41 ( Refer to Outline Drawing )			


- \*1. At Maximum Output Power, nominal input voltage, Ta = 25°C.
- \*2. For cases where conformance to various safety specs ( UL, CSA, EN ) are required, to be described as 100 - 240VAC, 50 / 60Hz on name plate.
- \*3. Not applicable for the in-rush current to Noise Filter for less than 0.2mS.
- \*4. Ripple & noise are measured at 20MHz by using a 12 inch twisted pair of load wires terminated with a 0.1uF Film Cap and a 47uF E-Cap.
- \*5. Measure line & load regulation at output terminal M3.5 tapped point.
- \*6. 85 - 264VAC, constant load.
- \*7. No load - Full load (Maximum power ), constant input voltage.
- \*8. Current limiting with automatic recovery.  
Avoid to operate at overload or dead short for more than 30 seconds.
- \*9. OVP circuit will shutdown output, manual reset (CNT reset or Re power on).
- \*10. Measured by each measuring method of UL and EN (at 60Hz), Ta = 25°C.
- \*11. Refer to Output Derating Curve (PA589-01-02\_) for details of output derating versus ambient temperature.
- \*12. Operating period at peak output current is less than 10sec., duty ≤ 0.35
- \*13. Standby input power refers to the power consumption during remote off and 5V is at no load condition.
- \*14. All parameters NOT specifically mentioned are measured at 230VAC input, rated load and Ta = 25°C.

**GWS250**

PA589-01-02

DERATING CURVE

**\*COOLING : CONVECTION COOLING**

Ta (°C)	LOAD (%)	STANDARD MOUNTING
-25 ~ +50	100	
70	50	

