

HWS150A/B

A259-01-01/B-B

SPECIFICATIONS

ITEMS		MODEL	HWS150A -12/B	HWS150A -15/B	HWS150A -24/B	HWS150A -48/B
1	Nominal Output Voltage	V	12	15	24	48
2	Maximum Output Current	A	13	10	6.5	3.3
3	Maximum Output Power	W	156.0	150.0	156.0	158.4
4	Efficiency (Typ.) (*1)	100VAC	% 85	% 86	% 88	% 89
		200VAC	% 88	% 89	% 90	% 91
5	Input Voltage Range (*2)	-	85 - 265VAC (47 - 63Hz) or 120 - 370VDC			
6	Input Current (Typ.) (*1)	A	1.9/0.95			
7	Inrush Current (Typ.) (*1)(*3)	-	14A at 100VAC, 28A at 200VAC, Ta=25°C, Cold Start			
8	PFHC	-	Designed to meet IEC61000-3-2			
9	Power Factor (Typ.) (*1)	-	0.98/0.93			
10	Output Voltage Range	V	9.6 - 14.4	12.0 - 18.0	19.2 - 28.8	38.4 - 52.8
11	Maximum Ripple & Noise (*4)	0≤Ta≤70°C	mV 150	mV 150	mV 150	mV 200
		-10≤Ta<0°C	mV 180	mV 180	mV 180	mV 240
12	Maximum Line Regulation (*5)	mV	48	60	96	192
13	Maximum Load Regulation (*6)	mV	96	120	150	240
14	Temperature Coefficient	-	Less than 0.02% / °C			
15	Over Current Protection (*7)	A	13.6 ≤	10.5 ≤	6.82 ≤	3.46 ≤
16	Over Voltage Protection (*8)	V	15.0 - 17.4	18.8 - 21.8	30.0 - 34.8	55.2 - 64.8
17	Hold-up Time (Typ.) (*1)	-	20ms			
18	Leakage Current (*9)	-	Less than 0.5mA. 0.2mA (Typ) at 100VAC / 0.4mA (Typ) at 230VAC			
19	Remote Sensing	-	-			
20	Parallel Operation	-	-			
21	Series Operation	-	Possible			
22	Operating Temperature (*10)	-	-10 to +70°C (-10 to +50°C:100%, +60°C:60%, +70°C:20%)			
23	Operating Humidity	-	30 to 90%RH (No Condensing)			
24	Storage Temperature	-	-30 to +85°C			
25	Storage Humidity	-	10 to 95%RH (No Condensing)			
26	Cooling	-	Convection Cooling			
27	Withstand Voltage	-	Input - FG : 2kVAC (20mA), Input - Output : 3kVAC (20mA) Output - FG : 500VAC (20mA) for 1min			
28	Isolation Resistance	-	More than 100MΩ at 25°C and 70%RH Output - FG : 500VDC			
29	Vibration	-	At no operating, 10 - 55Hz (Sweep for 1min) 19.6m/s ² Constant, X,Y,Z 1hour each.			
30	Shock	-	Less than 196.1m/s ²			
31	Safety	-	Approved by UL/CSA/EN62368-1, EN62477-1 (OVCI)(24V only), UL/CSA60950-1, EN60950-1 (Expire date of 60950-1 : 20/12/2020) Designed to meet Den-an Appendix 8 at 100VAC only.			
32	Line DIP	-	Designed to meet SEMI-F47 (200VAC Line only)			
33	Conducted Emission (*11)	-	Designed to meet EN55011/EN55032-B, FCC-B, VCCI-B			
34	Radiated Emission (*11)	-	Designed to meet EN55011/EN55032-B, FCC-B, VCCI-B			
35	Immunity (*11)	-	Designed to meet IEC61000-6-2 IEC61000-4-2, -3, -4, -5, -6, -8, -11			
36	Weight (Typ)	-	470g			
37	Size (W x H x D)	mm	37 x 82 x 160 (Refer to Outline Drawing)			

*Read instruction manual carefully, before using the power supply unit.

=NOTES=

- *1. At 100VAC/200VAC, Ta=25°C, nominal output voltage and maximum output power.
- *2. For cases where conformance to various safety specs (UL, CSA, EN) are required, to be described as 100 - 240VAC(50 - 60Hz).
- *3. Not applicable for the inrush current to Noise Filter for less than 0.2ms.
- *4. Measure with JEITA RC-9131B probe, Bandwidth of scope :100MHz.
- *5. 85 - 265VAC, constant load.
- *6. No load-Full load, constant input voltage.
- *7. Constant current limit and Hiccup with automatic recovery.
Avoid to operate at over load or short circuit condition.
- *8. OVP circuit will shut down output, manual reset (Re power on).
- *9. Measured by the each measuring method of UL, CSA, EN and Den-an (at 60Hz), Ta=25°C.
- *10. Output Derating
 - Derating at standard mounting. Refer to OUTPUT DERATING CURVE (A259-01-02).
 - Load (%) is percent of maximum output power or maximum output current, do not exceed its derating of maximum load.
- *11. The power supply is considered a component which will be installed into a final equipment.
The final equipment should be re-evaluated that it meets EMC directives.