

MESSRS :

Reliability Test Data

CUSTOMER'S PRODUCT NAME:

TDK-Lambda
PRODUCT NAME: DC/DC CONVERTER UNIT ALD-414012PJ133



TDK-Lambda Corporation

PREPARED BY	APPROVED BY	AUTHORIZED BY
<i>Mar.02 ,2012 Y.Miyaoka</i>	<i>Mar.02 ,2012 Y.Kimura</i>	<i>Mar.02 ,2012 H.Masuoka</i>

[1] Test Sample

ALD-414012PJ133 3pcs. for each

[2] Test Condition

Input Voltage Vin : 12.0 [V]
 Dimming Conditions Vbr : 0.0 [V] Max. Brightness
 ADIM: 0.0 [V] Max. Brightness
 Load RL : 240 [Ω]

[3] Result

The test result is shown on the next page. There was no problem.
 The measurement condition and Instrument depends on the following.

Measurement Condition

Input Voltage Vin : 12.0 [V]
 Dimming Conditions Vbr : 0.0 [V] Max. Brightness
 ADIM: 0.0 [V] Max. Brightness
 Load RL : 240 [Ω]
 Ambient temp Ta : 25 [$^{\circ}\text{C}$]

Measuring Instrument

Power supply : PAR160A(KIKUSUI) or equivalent
 Input DC current meter : R6841(ADVANTEST) or equivalent
 Output DC current meter : 187 (FLUKE) or equivalent
 Frequency counter : 187 (FLUKE) or equivalent

[4] Test Item

Item	Condition	Judgement Standard
High Temperature Continuous Operation	85 $^{\circ}\text{C}$, 500hrs.	Electrical and appearance should be in the spec.
Heat Shock	-40 $^{\circ}\text{C}$ <-> 85 $^{\circ}\text{C}$ 30min./each 100cycles	
Humidity Environment Off and on Operation	60 $^{\circ}\text{C}$ 90%R.H. On 1hr / Off 3hrs. 500cycles.	
Vibration	5~10Hz Amplitude 10mm 10~200Hz Accelerated Velocity 21.6m/s ² (2.2G) Log Sweep :10min. X,Y,Z direction 60min/each total 3hrs.	
Shock	588m/s ² (60G) 11ms Half-sine wave once each axis X,Y,Z,-X,-Y,-Z total 6times	

	No.	MATERIALS NAME	QU	MATERIAL	REMARK
	PRODUCT NAME or MODEL,TITLE				
	DC/DC CONVERTER UNIT ALD-414012PJ133				
TDK-Lambda	NAME OF DRAWING		DRAWING No.		PAGE
	Reliability Test Data		CTR-4356-X		1

High Temperature Continuous Operation

	No.	Iin [A]	Iout1-1 [mA]	Iout2-1 [mA]	Iout3-1 [mA]	Iout4-1 [mA]	F [Hz]
Before Test	1	1.40	144.9	144.8	142.2	143.9	193
	2	1.40	144.8	143.0	144.0	142.3	195
	3	1.42	146.4	145.0	143.9	144.0	199
After Test	1	1.41	145.4	145.5	142.8	145.0	193
	2	1.40	144.8	143.2	143.7	142.3	195
	3	1.42	146.2	144.8	143.5	144.0	197
Supper		1.6	168	168	168	168	240
Slower		0.95	112	112	112	112	160
Judgement		OK	OK	OK	OK	OK	OK

Heat Shock

	No.	Iin [A]	Iout1-1 [mA]	Iout2-1 [mA]	Iout3-1 [mA]	Iout4-1 [mA]	F [Hz]
Before Test	4	1.49	150.5	146.2	146.0	144.9	196
	5	1.42	144.6	142.5	142.9	144.3	196
	6	1.43	145.0	144.6	143.4	144.7	196
After Test	4	1.49	150.5	146.2	146.1	145.0	196
	5	1.42	144.6	142.6	142.9	144.4	196
	6	1.43	145.1	144.7	143.6	144.9	196
Supper		1.6	168	168	168	168	240
Slower		0.95	112	112	112	112	160
Judgement		OK	OK	OK	OK	OK	OK

Humidity Environment Off and on Operation

	No.	Iin [A]	Iout1-1 [mA]	Iout2-1 [mA]	Iout3-1 [mA]	Iout4-1 [mA]	F [Hz]
Before Test	7	1.36	140.4	143.2	140.5	143.5	198
	8	1.43	144.7	145.6	144.7	143.7	196
	9	1.45	144.3	146.7	145.2	146.9	194
After Test	7	1.37	141.4	143.2	140.6	143.9	198
	8	1.42	143.9	144.5	144.0	143.5	196
	9	1.45	144.5	146.8	145.2	147.3	195
Supper		1.6	168	168	168	168	240
Slower		0.95	112	112	112	112	160
Judgement		OK	OK	OK	OK	OK	OK

Vibration -> Shock

	No.	Iin [A]	Iout1-1 [mA]	Iout2-1 [mA]	Iout3-1 [mA]	Iout4-1 [mA]	F [Hz]
Before Test	10	1.40	146.2	140.2	143.6	142.6	198
	11	1.41	144.1	143.0	143.6	141.5	195
	12	1.46	148.8	146.6	143.2	145.3	199
After Test	10	1.42	147.0	141.0	144.6	143.6	198
	11	1.42	142.6	141.3	141.9	140.0	195
	12	1.43	147.6	145.4	142.2	144.3	199
Supper		1.6	168	168	168	168	240
Slower		0.95	112	112	112	112	160
Judgement		OK	OK	OK	OK	OK	OK

TDK-Lambda	No.	MATERIALS NAME	QU	MATERIAL	REMARK
	PRODUCT NAME or MODEL, TITLE				
	DC/DC CONVERTER UNIT ALD-414012PJ133				
	NAME OF DRAWING		DRAWING No.		PAGE
Reliability Test Data		CTR-4356-X		2	

<The drawings may be changed without any notice.>