



- NOTE
1. MATING PLUG P/N MC1.5/5-ST-3.81 PHOENIX.
  2. MOUNTING HOLES FOR SLIDE P/N CC3001-00-S160 GENERAL DEVICES OR EQUIVALENT. USE 3x#10-32x038 inch SCREWS FOR EACH SLIDE. ENSURE THAT THE SCREWS DO NOT PENETRATE MORE THAN 6.0 mm INTO THE UNIT.
  3. AC INPUT RATING AND SAFETY APPROVAL SYMBOLS ARE SHOWN HERE IN ACCORDING TO THE SPECIFICATION.
  4. STRAIN RELIEF DEVICE P/N: 1576.16.11 AGRO.
  5. MODEL NAME AND OUTPUT RATING ARE SHOWN HERE ACCORDING TO THE SPECIFICATION.
  6. MOUNTING HOLES FOR 19" RACK, USE M6x16 SCREWS TO FIX THE UNIT TO THE RACK.
  7. MATING PLUG P/N IMC1.5/7-ST-3.81 PHOENIX.
  8. COMPANY LOGO IS SHOWN HERE.

ACCESSORIES

ITEM	PART NUMBER	QTY	PACKING	OUTER PACKING	NOTE
LINKING CABLE	IA575-81-11_	1	PLASTIC BAG		
DB25 PLUG KIT	749809-9 AMP	1	PLASTIC BAG		
STRAIN RELIEF BRACKET	IA575-32-07-00_	1	NONE		
STRAIN RELIEF	1576.16.11 AGRO	1			
STRAIN RELIEF WASHER	8216 AGRO	1			
FLAT HEAD SCREW M3x8		3	PLASTIC BAG		
PROT. BRACKET ASSEMBLY	IA575-32-15-00_	1			
AUXILIARY CONNECTOR PLUG	IA669-81-14_	1	PLASTIC BAG		CONNECTOR PLUG IMC 1.5/7-ST-3.81+LABEL
PLUG HOUSING	KGG-MC 1.5/7	1			

(unit : mm)

MODEL NAME	GEN2400W 150-600V 1PH&3PH
<b>TDK-Lambda</b>	

IA669-02-02D